

Control switch Ex

HOME > KATEGORIE > CASSETTES, PUSH BUTTONS AND CONTROL PANELS EX > ATEX ZONE > CONTROL SWITCH EX

High-quality signalling components are indispensable during panel assembly. This product group includes indicator lights, ammeters, labels, cam switches, pushbuttons, control switches and much more. There is the possibility of ad hoc connection to indicator or control elements (mounting in walls with a maximum thickness of 5 mm).

BASIC DATA:

- Click ring for quick installation
- Complete certification of embedded components
- Various connection terminals
- Dimension of the standard working element Ø 30.5 mm

TECHNICAL DATA:

- Marking according to 94/9/EC (ATEX) D II 2G Ex ed IIC T6 / D I M 2 Ex de I
- EC type examination certificate PTB 98 ATEX 1117 U1)
- Permissible ambient temperature -20°C to +40°C / -55°C to +45°C (optional)
- Rated voltage up to 690 V AC
- Rated current up to 20 A
- Rated current, gold-plated contacts up to 0.4 A
- Rated switching capacity and insulation according to EN 60947-5-1 AC-3: Ue 230 V / Ie 8 A; EU 400V/Ie 6A; AC-11: Ue 24V/Ie 6A; Ue 230 V / Ie 0.4 A
- Connection terminals 2-2.5 mm² stranded, 6 mm² single-wire
- Weight 0.55 kg
- Mounting method Ø 30.5 mm mounting hole
- Housing color gray

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



DOKUMENTY



Data sheet [Kliknij aby pobrać](#)

Lp. **Description** **Catalogue no.**

1 Control switch 5.GHG 249

