

RU - Tilt frame

HOME > KATEGORIE > INTERNAL BUILDING SYSTEMS > RU - TILT FRAME


It is used for mounting 19" devices in enclosures of 800 mm width. Available in the symmetrical and asymmetrical version. Locked by D5 lock with espagnolette bars. The frame has process openings allowing to change the opening direction. Frame bearing capacity - 160 kg.

Maximum mounting depth:

- symmetrical frame: 360 mm,
- asymmetrical frame: 440 mm.

Made of steel sheet and profiles, painted on RAL7035_GS colour.

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



RU - 19" Tilt frame for RSB, SZB

Lp.	Description - Enclosure dimensions Rack Unit height	Catalogue No. symmetrical	Catalogue No. asymmetrical
1	RU-1400 - 24U	132-001	133-001
2	RU-1600 - 28U	132-002	133-002
3	RU-1800 - 33U	132-003	133-003
4	RU-2000 - 37U	132-004	133-004

RUR - 19" Tilt frame for RR

Lp.	Description - Enclosure dimensions Rack Unit height	Catalogue No. symmetrical	Catalogue No. asymmetrical
1	RUR-1200 - 20U	132-100	133-100
2	RUR-1600 - 29U	132-101	133-101
3	RUR-1800 - 34U	132-102	133-102
4	RUR-2000 - 38U	132-103	133-143
5	RUR-2200 - 43U	132-104	133-104