

SlimLine Pro

HOME > KATEGORIE > AIR CONDITIONING CONTROL CABINETS > SLIMLINE PRO

The innovative one man mounting systems from Seifert allows a screw less installation with no need of additional fixing material. Depending on the size of the unit the mounting time can be reduced to less than 2 minutes. Simplified cutouts without the need of drilling holes into the enclosure, ease the mounting even further. All models have an integrated condensate evaporation, an electronic controller with color display, a temperature range from 10°C to 60°C and an ingress protection class of IP 56. They also comply to NEMA / UL type 3, 3R, 12, 4 and 4X (stainless steel models).

With cooling capacities from 350 W to 6.2 kW they cover a big range of applications. We have also placed a strong emphasis in standardizing components, versions and sizes thus diminishing the need of large spare part stocks, complex training or long unit selection processes. All SlimLine Pro units come in powder coated mild steel housing, RAL 7035. For applications where hygiene and corrosion protection are required, we offer different grades of stainless steel housings. SlimLine Pro air conditioners can be wall mounted or installed recessed.

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI





Lp.	Type - Cooling capacity L35L35 / L35L50 (DIN 3168)	Voltage / Frequency	Dimensions (W × H × D mm)	Catalogue No.
1	KG 8503 - 350 W / 200 W	230 V – 50/60 Hz	250 x 600 x 135	5.850300001
2	KG 8505 - 550 W / 410 W	230 V – 50/60 Hz	520 x 370 x 155	5.850500001
3	KG 8506 - 670 W / 435 W	230 V – 50/60 Hz	250 x 600 x 135	5.850600001
4	KG 8508 - 825 W / 820 W	230 V – 50/60 Hz	305 x 950 x 210	5.850800001
5	KG 8508 - 825 W / 820 W	400/460 V – 50/60 Hz 3~	305 x 950 x 210	5.850820001
6	KG 8512 - 1,2 kW / 900 W	230 V – 50/60 Hz	305 x 950 x 210	5.851200001
7	KG 8512 - 1,2 kW / 900 W	400/460 V – 50/60 Hz 3~	305 x 950 x 210	5.851220001
8	KG 8412 - 1,5 kW / 1,27 kW	230 V – 50/60 Hz	395 x 950 x 250	5.841200001
9	KG 8412 - 1,5 kW / 1,27 kW	400/460 V – 50/60 Hz 3~	395 x 950 x 250	5.841220001
10	KG 8515 - 1,5 kW / 1,3 kW	230 V – 50/60 Hz	395 x 1350 x 210	5.851500001
11	KG 8515 - 1,5 kW / 1,3 kW	400/460 V – 50/60 Hz 3~	395 x 1350 x 210	5.851520001
12	KG 8520 - 2,0 kW / 1,5 kW	230 V – 50/60 Hz	395 x 1350 x 210	5.852000001
13	KG 8520 - 2,0 kW / 1,5 kW	400/460 V – 50/60 Hz 3~	395 x 1350 x 210	5.852020001
14	KG 8525 - 2,5 kW / 2,1 kW	230 V – 50/60 Hz	395 x 1350 x 210	5.852500001
15	KG 8525 - 2,5 kW / 2,1 kW	400/460 V – 50/60 Hz 3~	395 x 1350 x 210	5.852520001
16	KG 8540 - 4,0 kW / 3,5 kW	400/460 V – 50/60 Hz 3~	455 x 1550 x 270	5.854000001
17	KG 8562 - 6,0 kW / 5,0 kW	400/460 V – 50/60 Hz 3~	455 x 1630 x 270	5.856220001

