

Small 19 inch enclosure - NK 1 IP 20

HOME > KATEGORIE > SMALL 19-INCH ENCLOSURE - NK-1 IP 20

NK-1 – is a wall-mounted or standing enclosure, used for assembly of small network systems in 19-inch spacing.

Type	Corrosivity category	Material	Coating
NRS-2	C2	steel sheet	RAL7035

GENERAL INFORMATION:

- Ingress protection according to IP code: 20
- Impact resistance according to IK code: 10
- Operating temperature range: 0 – +80°C

BASIC DATA:

- Body: monobloc type, welded
- Closure: hinged door with 105° opening angle; the possibility of independent change of the door opening direction; enclosures up to 500 mm height have one 1333 patent lock whereas higher enclosures have two locks of the same type
- 19-inch rack: single; perforated, made of 2 mm thick galvanized steel sheet, adjustable on the entire depth of the enclosure.

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



KARTA KATALOGOWA

DOKUMENTY



Declaration of compliance for Radiolex products [Kliknij aby pobrać](#)

The following table presents enclosures according to the description.

Lp.	Wymiary (szer. x wys. x gł., mm)	Catalogue No. transparent door	Catalogue No. steel door
1	600 × 320 × 400 – 6U	405-001	406-001
2	600 × 500 × 400 – 10U	405-002	410-002
3	600 × 600 × 400 – 12U	405-003	410-003
4	600 × 720 × 400 – 15U	405-004	410-004
5	600 × 850 × 400 – 18U	405-005	410-005
6	600 × 320 × 500 – 6U	405-006	410-006
7	600 × 500 × 500 – 10U	405-007	410-007
8	600 × 600 × 500 – 12U	405-008	410-008
9	600 × 720 × 500 – 15U	405-009	410-009
10	600 × 850 × 500 – 18U	405-010	410-010
11	600 × 320 × 600 – 6U	405-011	410-011
12	600 × 500 × 600 – 10U	405-012	410-012
13	600 × 600 × 600 – 12U	405-013	410-013
14	600 × 720 × 600 – 15U	405-014	410-014
15	600 × 850 × 600 – 18U	405-015	410-015

