

Small double section 19 inch enclosure - NK 2 IP 20

HOME > KATEGORIE > SMALL DOUBLE SECTION 19-INCH ENCLOSURE - NK-2 IP 20

NK-2 – is a double section wall-mounted enclosure, used for assembly of small network systems in 19-inch spacing.

Type	Corrosivity category	Material	Coating
NK-2	C2	steel sheet	RAL7035

GENERAL INFORMATION:

- Ingress protection according to IP code: 20
- Impact resistance according to IK code: 10
- Operating temperature range: 0 – +80°C

BASIC DATA:

- Body: monobloc type, welded
- Closure: hinged door with 105° opening angle; the possibility of independent change of the door opening direction; enclosures up to 500 mm height have one 1333 patent lock whereas higher enclosures have two locks of the same type
- 19-inch rack: single; perforated, made of 2 mm thick galvanized steel sheet.

SCOPE OF DELIVERY:

- Assembled enclosure with a key.

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



KARTA KATALOGOWA

DOKUMENTY



Declaration of compliance for Radiolex products [Kliknij aby pobrać](#)

The following table presents enclosures according to the description.

Lp.	Wymiary (szer. x wys. x gł., mm)	Catalogue No. transparent door	Catalogue No. steel door
1	600 × 320 × 500/350 - 6U	407-001	408-001
2	600 × 500 × 500/350 - 10U	407-002	408-002
3	600 × 600 × 500/350 - 12U	407-003	408-003
4	600 × 720 × 500/350 - 15U	407-004	408-004
5	600 × 850 × 500/350 - 18U	407-005	408-005

