

STL IP 20 – Standard IT enclosure

HOME > KATEGORIE > STEERING CABINETS > STL IP 20 – STANDARD IT ENCLOSURE

STL – is a standing enclosure, used for assembly of network systems in 19-inch spacing. Applies to the separation of larger IT networks. The enclosure thanks to technological openings can be freely combined in series.

Type	Corrosivity category	Material / additional description	Coating
STL	C2	steel sheet / steel or transparent door	RAL7035
STL-SE	C2	steel sheet / perforated door	RAL9005

GENERAL INFORMATION:

- Ingress protection according to IP code: 20
- Impact resistance according to IK code: 10
- Operating temperature range: -40 – +80°C

BASIC DATA:

- Closure: steel, transparent or perforated – hinged door with 105° opening angle; the possibility of independent change of the door opening direction; STL enclosures are equipped with two 1333 type patent locks; STL-SE with lock in the form of a handle with the possibility of mounting a latch insert with a key
- 19-inch rack: double; made of 2 mm thick galvanized steel sheet
- Cable entry: there are gland plates in the top and bottom, its dimensions depend on the width of the enclosure
- Grounding: threaded grounding studs in the door and enclosure body

ADDITIONAL OPTIONS:

- Unusual dimensions
- Painting to any color according to the RAL palette

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



DOKUMENTY



CATALOGUE CARD [Kliknij aby pobrać](#)



Declaration of compliance for Radiolex products [Kliknij aby pobrać](#)



Powder coatings maintenance instructions [Kliknij aby pobrać](#)

The following table presents enclosures according to the description.

Lp.	Wymiary (szer. x wys. x gł., mm)	Catalogue No. transparent door	Catalogue No. steel door
1	800 × 2220 × 1000 - 47U	430-001	431-001
2	800 × 2220 × 800 - 47U	430-002	431-002
3	800 × 2220 × 600 - 47U	430-003	431-003
4	600 × 2220 × 1000 - 47U	430-004	431-004
5	600 × 2220 × 800 - 47U	430-005	431-005
6	600 × 2220 × 600 - 47U	430-006	431-006
7	800 × 2135 × 1000 - 45U	430-007	431-007
8	800 × 2135 × 800 - 45U	430-008	431-008
9	800 × 2135 × 600 - 45U	430-008	431-009
10	600 × 2135 × 1000 - 45U	430-010	431-010
11	600 × 2135 × 800 - 45U	430-011	431-011
12	600 × 2135 × 600 - 45U	430-012	431-012
13	800 × 2000 × 1000 - 42U	430-013	431-013
14	800 × 2000 × 800 - 42U	430-014	431-014
15	800 × 2000 × 600 - 42U	430-015	431-015
16	600 × 2000 × 1000 - 42U	430-016	431-016
17	600 × 2000 × 800 - 42U	430-017	431-017
18	600 × 2000 × 600 - 42U	430-018	431-018
19	800 × 1865 × 800 - 39U	430-019	431-019
20	800 × 1865 × 600 - 39U	430-020	431-020
21	600 × 1865 × 800 - 39U	430-021	431-021
22	600 × 1865 × 800 - 39U	430-022	431-022
23	800 × 1735 × 800 - 36U	430-023	431-023
24	800 × 1735 × 600 - 36U	430-024	431-024
25	600 × 1735 × 800 - 36U	430-025	431-025
26	600 × 1735 × 600 - 36U	430-026	431-026
27	800 × 1600 × 800 - 33U	430-027	431-027
28	800 × 1600 × 600 - 33U	430-028	431-028
29	600 × 1600 × 800 - 33U	430-029	431-029
30	600 × 1600 × 600 - 33U	430-030	431-030
31	800 × 1465 × 800 - 30U	430-031	431-031
32	800 × 1465 × 600 - 30U	430-032	431-032
33	600 × 1465 × 800 - 30U	430-033	431-033
34	600 × 1465 × 600 - 30U	430-034	431-034
35	800 × 1335 × 800 - 27U	430-035	431-035
36	800 × 1335 × 600 - 27U	430-036	431-036
37	600 × 1335 × 800 - 27U	430-037	431-037
38	600 × 1335 × 600 - 27U	430-038	431-038
39	800 × 1200 × 800 - 24U	430-039	431-039
40	800 × 1200 × 600 - 24U	430-040	431-040
41	600 × 1200 × 800 - 24U	430-041	431-041
42	600 × 1200 × 600 - 24U	430-042	431-042
43	800 × 935 × 800 - 18U	430-042	431-043
44	800 × 935 × 600 - 18U	430-044	431-044
45	600 × 935 × 800 - 18U	430-045	431-045
46	600 × 935 × 600 - 18U	430-046	431-046
47	800 × 800 × 800 - 15U	430-047	431-047
48	800 × 800 × 600 - 15U	430-048	431-048
49	600 × 800 × 800 - 15U	430-049	431-049
50	600 × 800 × 600 - 15U	430-050	431-050

The following table presents enclosures according to the description

Lp.	Wymiary (szer. x wys. x gł., mm)	Catalogue No. front door	Catalogue No. front and back door
1	800 × 2220 × 1200 - 47U	441-001	442-001
2	800 × 2220 × 1000 - 47U	441-002	442-002
3	600 × 2220 × 1200 - 47U	441-003	442-003
4	600 × 2220 × 1000 - 47U	441-004	442-004
5	800 × 2135 × 1200 - 45U	441-005	442-005
6	800 × 2135 × 1000 - 45U	441-006	442-006
7	600 × 2135 × 1200 - 45U	441-007	442-007
8	600 × 2135 × 1000 - 45U	441-008	442-008
9	800 × 2000 × 1200 - 42U	441-009	442-009
10	800 × 2000 × 1000 - 42U	441-010	442-010
11	600 × 2000 × 1200 - 42U	441-011	442-011
12	600 × 2000 × 1000 - 42U	441-012	442-012
13	800 × 1865 × 1200 - 39U	441-013	442-013
14	800 × 1865 × 1000 - 39U	441-014	442-014
15	600 × 1865 × 1200 - 39U	441-015	442-015
16	600 × 1865 × 1000 - 39U	441-016	442-016
17	800 × 1735 × 1200 - 36U	441-017	442-017
18	800 × 1735 × 1000 - 36U	441-018	442-018
19	600 × 1735 × 1200 - 36U	441-019	442-019
20	600 × 1735 × 1000 - 36U	441-020	442-020