

UD RR - Roof for Rack Enclosure

HOME > KATEGORIE > EXTERNAL BUILDING SYSTEMS > UD-RR - ROOF FOR RACK ENCLOSURE

It is used for covering top panel of a row or a single Rack Enclosure (RR). Improves tightness of the enclosure when it consist of a roof ventilation system. Offered in two versions: internal or external. The internal side cover does not increase the overall dimension of the enclosure.

SYMBOLS OF TYPES

- UD-RR - Roof with roof bushing
- UD-RRZ - External roof
- UD-RRW - Internal roof
- UD-RRZ-OH - Stainless steel 1.4301 (AISI 304) external roof
- UD-RRW-OH - Stainless steel 1.4301 (AISI 304) internal roof
- UD-RRZ-KO - Acid-proof steel 1.4404 (AISI 316L) external roof
- UD-RRW-KO - Acid-proof steel 1.4404 (AISI 316L) internal roof
- UD-RRO - Pressed and perforated roof
- UD-RROZ - External roof

- UD-RROW – Internal roof
- UD-RROZ-OH – Stainless steel 1.4301 (AISI 304) external roof
- UD-RROW-OH – Stainless steel 1.4301 (AISI 304) internal roof
- UD-RROZ-KO – Acid-proof steel 1.4404 (AISI 316L) external roof
- UD-RROW-KO – Acid-proof steel 1.4404 (AISI 316L) internal roof

It is used for covering top plate of Rack Enclosure. Improves tightness of enclosure when used with roof ventilation system. Offered in the asymmetrical left and right versions. Asymmetrical roof increases the overall dimensions of the enclosure on one side.

- UD-RR-AS – Asymmetrical roof with roof bushing
- UD-RR-ASL – Asymmetrical roof, left version
- UD-RR-ASP – Asymmetrical roof, right version
- UD-RR-ASL-OH – Stainless steel 1.4301 (AISI 304) asymmetrical roof, left version
- UD-RR-ASP-OH – Stainless steel 1.4301 (AISI 304) asymmetrical roof, right version
- UD-RR-ASL-KO – Acid-proof steel 1.4404 (AISI 316L) asymmetrical roof, left version
- UD-RR-ASP-KO – Acid-proof steel 1.4404 (AISI 316L) asymmetrical roof, right version

- UD-RRO-AS – Pressed and perforated asymmetrical roof
- UD-RRO-ASL – Asymmetrical roof, left version
- UD-RRO-ASP – Asymmetrical roof, right version
- UD-RRO-ASL-OH – Stainless steel 1.4301 (AISI 304) asymmetrical roof, left version
- UD-RRO-ASP-OH – Stainless steel 1.4301 (AISI 304) asymmetrical roof, right version
- UD-RRO-ASL-KO – Acid-proof steel 1.4404 (AISI 316L) asymmetrical roof, left version
- UD-RRO-ASP-KO – Acid-proof steel 1.4404 (AISI 316L) asymmetrical roof, right version

OZNACZENIA SYMETRII /BRAK TŁUMACZENIA

/BRAK TŁUMACZENIA

Dopisek „W” – oznacza, że dach licuje się z ramą (nie wystaje ponad obrys obudowy)

Dopisek „**Z**” – oznacza, że dach wystaje ponad obrys obudowy z obu stron (stosowany w przypadku, gdy obudowa jest pojedyncza oraz ma zastosowane boki zewnętrzne, które poszerzają gabaryt obudowy)

Dopisek „**L**” – oznacza, że dach z lewej strony wystaje ponad obrys obudowy, a z prawej licuje się z ramą

Dopisek „**P**” – oznacza, że dach z prawej strony wystaje ponad obrys obudowy, a z lewej licuje się z ramą

OZNACZENIA MATERIAŁÓW

/BRAK TŁUMACZENIA

Dach bez dodatkowego oznaczenia produkowany jest z blachy ocynkowanej, malowany proszkowo na kolor RAL7035_GS

Dach z oznaczeniem „**OH**” – produkowany jest ze stali nierdzewnej 1.4301 (AISI 304)

Dach z oznaczeniem „**KO**” – produkowany jest ze stali kwasoodpornej 1.4404 (AISI 316L)

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



UD-RR - Dach obudowy ramowej na tulejach (symetryczny)

Lp.	Description - enclosure dimensions (W × D mm)	Catalogue No. UD-RRZ	Catalogue No. UD-RRW	Catalogue No. UD-RRZ-OH	Catalogue No. UD-RRW-OH	Catalogue No. UD-RRZ-KO	Catalogue No. UD-RRW-KO
1	UD-RR - 400 × 400	198-001	198-020	199-001	199-020	199-201	199-220
2	UD-RR - 400 × 500	198-002	198-021	199-002	199-021	199-202	199-221
3	UD-RR - 400 × 600	198-003	198-022	199-003	199-022	199-203	199-222
4	UD-RR - 600 × 400	198-004	198-023	199-004	199-023	199-204	199-223
5	UD-RR - 600 × 500	198-005	198-024	199-005	199-024	199-205	199-224
6	UD-RR - 600 × 600	198-006	198-025	199-006	199-025	199-206	199-225
7	UD-RR - 600 × 800	198-007	198-026	199-007	199-026	199-207	199-226
8	UD-RR - 800 × 400	198-008	198-027	199-008	199-027	199-208	199-227
9	UD-RR - 800 × 500	198-009	198-028	199-009	199-028	199-209	199-228
10	UD-RR - 800 × 600	198-010	198-029	199-010	199-029	199-210	199-229
11	UD-RR - 800 × 800	198-011	198-030	199-011	199-030	199-211	199-230
12	UD-RR - 1000 × 400	198-012	198-031	199-012	199-031	199-212	199-231
13	UD-RR - 1000 × 500	198-013	198-032	199-013	199-032	199-213	199-232
14	UD-RR - 1000 × 600	198-014	198-033	199-014	199-033	199-214	199-233
15	UD-RR - 1000 × 800	198-015	198-034	199-015	199-034	199-215	199-234
16	UD-RR - 1200 × 400	198-016	198-035	199-016	199-035	199-216	199-235
17	UD-RR - 1200 × 500	198-017	198-036	199-017	199-036	199-217	199-236
18	UD-RR - 1200 × 600	198-018	198-037	199-018	199-037	199-218	199-237
19	UD-RR - 1200 × 800	198-019	198-038	199-019	199-038	199-219	199-238

UD-RRO - Dach obudowy ramowej z perforacją (symetryczny)

Lp.	Description - enclosure dimensions (W × D mm)	Catalogue No. UD-ROZ	Catalogue No. UD-RROW	Catalogue No. UD-RROZ-OH	Catalogue No. UD-RROW-OH	Catalogue No. UD-RROZ-KO	Catalogue No. UD-RROW-KO
1	UD-RRO - 400 × 400	198-101	198-120	199-101	199-120	199-301	199-320
2	UD-RRO - 400 × 500	198-102	198-121	199-102	199-121	199-302	199-321
3	UD-RRO - 400 × 600	198-103	198-122	199-103	199-122	199-303	199-322
4	UD-RRO - 600 × 400	198-104	198-123	199-104	199-123	199-304	199-323
5	UD-RRO - 600 × 500	198-105	198-124	199-105	199-124	199-305	199-324
6	UD-RRO - 600 × 600	198-106	198-125	199-106	199-125	199-306	199-325
7	UD-RRO - 600 × 800	198-107	198-126	199-107	199-126	199-307	199-326
8	UD-RRO - 800 × 400	198-108	198-127	199-108	199-127	199-308	199-327
9	UD-RRO - 800 × 500	198-109	198-128	199-109	199-128	199-309	199-328
10	UD-RRO - 800 × 600	198-110	198-129	199-110	199-129	199-310	199-329
11	UD-RRO - 800 × 800	198-111	198-130	199-111	199-130	199-311	199-330
12	UD-RRO - 1000 × 400	198-112	198-131	199-112	199-131	199-312	199-331
13	UD-RRO - 1000 × 500	198-113	198-132	199-113	199-132	199-313	199-332
14	UD-RRO - 1000 × 600	198-114	198-133	199-114	199-133	199-314	199-333
15	UD-RRO - 1000 × 800	198-115	198-134	199-115	199-134	199-315	199-334
16	UD-RRO - 1200 × 400	198-116	198-135	199-116	199-135	199-316	199-335
17	UD-RRO - 1200 × 500	198-117	198-136	199-117	199-136	199-317	199-336
18	UD-RRO - 1200 × 600	198-118	198-137	199-118	199-137	199-318	199-337
19	UD-RRO - 1200 × 800	198-119	198-138	199-119	199-138	199-319	199-338