

COMPACT OUTDOOR



Description

Order Number:	876221201
Brand Name:	COMPACT OUTDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 56 / Type 12, 3, 3R, 4
Included:	With enclosure heater and aluminium filter
Approvals:	CE, cURus, cULus

Technical Data

Cooling capacity L35L35:	5.8 kW @ 50 Hz 6.2 kW @ 60 Hz
Cooling capacity L35L50:	4.8 kW @ 50 Hz 5.4 kW @ 60 Hz
Enclosure heater:	2,000 W
Compressor type:	Scroll Compressor
Refrigerant / GWP:	R134a / 1430
Operating Temperature Range:	-40°C - 55°C
Air flow volume (system / unimpeded):	Ambient: 1080 / 1480 m ³ /h Enclosure: 935 / 1080 m ³ /h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	1135 x 455 x 390 mm
Weight:	85 kg
Current L35L35:	5.9 A @ 50 Hz 6.2A @ 60 Hz
Starting current:	57 / 44 A
Max. current:	9.8 A
Nominal power L35L35:	3.0 kW @ 50 Hz 3.8 kW @ 60 Hz
Max. power:	6.3 kW
Short-circuit current rating:	5 kA
Connection:	4 pole terminal block for power 5 pole terminal block for signals, 3 pole connector for RS 485 interface

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group COMPACT OUTDOOR - cooling units NEMA / Type 4X](#)

Order Information

Box dimensions	1215 x 555 x 549.5 mm
Gross weight	96.5 Kg
Taric code	84158200